



PART NO.	WIDTH "W"	"T" APPLICATION THICKNESS RANGE
MCCGF-1N	.19 (4.8)	.025-.045 (0.6-1.1)
MCCGF-2N		.044-.056 (1.1-1.4)
MCCGF-3N		.055-.069 (1.4-1.7)

NOTES

1. LENGTH: 100 FT (30.5 M) REELS.
2. MATERIAL: 304 STAINLESS STEEL.  
COATING: FUSION BONDED NYLON WITH CUSHION.  
COLOR: BLACK.
3. TABER ABRASION RESISTANCE: 1KG LOAD, C17 WHEEL  
SUBSTRATE FINISH: 5 TO 8 mg LOSS AFTER 100 CYCLES  
POLYMER CHUSION: 25 mg LOSS AFTER 1000 CYCLES.
3. POLYMER CUSHION: 46 DUROMETER, SHORE D, BLACK.
4. DIELECTRIC STRENGTH: 1200 VOLTS @ 60 HZ.
5. HEAT CONTINUOUS: 185°F (85°C).
6. SALT SPRAY TESTING: PER ASTM B117. MIL-STD-202, METHOD 301-2000 HOURS.
7. FLAMMABILITY: UL94-VO YELLOW CARD NO. E113553 NZMT2.
8. RANDOM VIBRATION: MIL-STD-1344 METHOD 2005.1, TEST CONDITIONS VI LETTER J.  
DURATION 8 HOURS LONGITUDINAL AND 8 HOURS PERPENDICULAR.  
rms G 41.7

REV		DESCRIPTION		ENGR DATE		TITLE: METAL CONTINUOUS CUSHION GROMMET, FLEXIBLE			DWG IN IN (MM)		FINAL		PRINT TYPE	
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°		FILE # MCCGF		DWN: S.M.		APP:		PART #		MCCGF SERIES		CA		
MAT'L: SEE NOTES		RE: RICHCO, INC.		DT: 08.01.02		DT:		RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060						